



RECOMMENDED FFC/FPC DIM.

- SPEC :
- Housing: High-Temp Plastic, UL94-V
Color: Nature
 - Locker: High-Temp Plastic, UL94-V
Color: Coffee
 - Contact: Phosphor Bronze
Initial: 30m Ohms Max.
Voltage Rating: 50V AC, DC
 - Solder Tab: BRASS
 - Temperature Rating: -25°C ~ +85°C
 - Dielectric Withstanding Voltage: 500V AC/Min

● : 表示現有提供PIN數

PIN	DIM.A	DIM.B	DIM.C	DIM.D
4	9.1	3.0	11.0	5.1
5	10.1	4.0	12.0	6.1
6	11.1	5.0	13.0	7.1
7	12.1	6.0	14.0	8.1
8	13.1	7.0	15.0	9.1
9	14.1	8.0	16.0	10.1
10	15.1	9.0	17.0	11.1
11	16.1	10.0	18.0	12.1
12	17.1	11.0	19.0	13.1
13	18.1	12.0	20.0	14.1
14	19.1	13.0	21.0	15.1
15	20.1	14.0	22.0	16.1
16	21.1	15.0	23.0	17.1
17	22.1	16.0	24.0	18.1
18	23.1	17.0	25.0	19.1
19	24.1	18.0	26.0	20.1
20	25.1	19.0	27.0	21.1
21	26.1	20.0	28.0	22.1
22	27.1	21.0	29.0	23.1
23	28.1	22.0	30.0	24.1
24	29.1	23.0	31.0	25.1
25	30.1	24.0	32.0	26.1
26	31.1	25.0	33.0	27.1
27	32.1	26.0	34.0	28.1
28	33.1	27.0	35.0	29.1
29	34.1	28.0	36.0	30.1
30	35.1	29.0	37.0	31.1

ORDERING INFORMATION:

FPCZ - 10250 DHUE - xx - x - x

- PLATING: T=TIN G=GOLD FLASH
- PACKING T=TUBE R=REEL
- NO. of contacts
- Series name
- PITCH=1.0mm
- FPC SERIES



鼎掄實業有限公司
DINGLUN INDUSTRIAL CO. LTD.

TITLE FPC 1.0PH 2.5H 抽屜式上接

DRAWN: *michael lin*
2017/07/22

TOLERANCE SCALE
.X±0.30 None

P/N NO. FPCZ-10250DHUE-xx-xx

CHECKED: *Eddie Liu*
2017/07/22

.XX±0.20 UNIT
.XXX±0.10 mm

DWG. NO.

APPROVED: *Eddie Liu*
2017/07/23

PROJECTION REV.
A

CUSTOMER P/N NO.

REV.	REASONS	DATE	DRAWN
1			
2			
3			
4			

1

2

3

4

5

6

7

8

9